



CC-single cores PUR-390

无卤型，耐低温，1kV

ConCab kabel gmbh



应用领域

CC-single core PUR-390 适合用作安装导线，要求无卤并且抗机械应力的。绝缘材料极其耐油脂、酸和碱。

application

The CC-single core PUR-390 is suitable for installation purposes requiring zero halogen and resistant to mechanical stress. The insulation is extensively resistant to oil, fat, acid and lye.

构造

纯铜丝或镀锡铜丝多股精绞，PUR 芯线绝缘，无卤，耐低温和阻燃（符合 DIN EN 60332-1-2 VDE 0482 332-1-2:2005-06 部分标准）。单色和绿黄。

construction

Bare or tinned fine strands of copper wire, PUR core insulation, halogen-free, cold-resistant und flame retardant (acc. to DIN EN 60332-1-2 VDE 0482 part 332-1-2:2005-06). Single colour and greenyellow.

技术数据 / technical data

额定电压 / rated voltage:	1000 V
测试电压 / test voltage:	3000 V
导体绞合方式 / conductor stranding:	纯铜绞合 / fine copper strands, 符合 / acc. to DIN VDE 0295, 5 类标准 / class 5
绝缘阻抗 / insulation resistance:	min. 10 MOhm x km
温度范围 / temperature range:	固定安装 / fixed installation: -40° C 至 /to +80° C
弯曲半径 / bending radius:	固定安装 / fixed installation: 10 x d 外径 -ø / outer-ø
符合标准 / approvals:	按照 / acc. to DIN VDE 0285

Robust-Ltg.

Schleppflex®

BUS-Ltg.

Steuer-Ltg.

Daten-Ltg.

IT/Kommunik.

Hochtemp.-Ltg.

Aufzugs-Ltg.

Gummi-Ltg.

Einzel-Adern


Spiralkabel

Kabel-Zubehör

Technik-Anhang

CC-single core PUR-390

halogen-free, cold resistant, 1kV



物料编码 part-no.	芯线数 / 导体截面积 no. of cores / cross-section	铜重 copper weight kg/km	外径 outer-Ø d mm	电缆重量 weight kg/km
390 0005 ...	0,50	5	2,2	8
390 0007 ...	0,75	8	2,4	11
390 0010 ...	1,0	10	2,6	13
390 0015 ...	1,5	15	3,1	19
390 0025 ...	2,5	24	3,7	32
390 0040 ...	4	38	4,4	45
390 0060 ...	6	58	5,2	65
390 0100 ...	10	96	6,8	115
390 0160 ...	16	154	7,8	178
390 0250 ...	25	240	10,2	250
390 0350 ...	35	336	11,6	335
390 0500 ...	50	480	13,2	500
390 0700 ...	70	672	15,5	690
390 0950 ...	95	912	17,8	915
390 1200 ...	120	1.152	19,4	1.060
390 1500 ...	150	1.440	22,3	1.370

物料编码 / part no.:	390	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
导体截面积 / cross-section	-----						
导体 / conductor							
纯铜丝 / Cu bare							0
镀锡铜丝 / Cu tinned							1
颜色编码 / colour code							
(按照颜色表格 / acc. to colour table)							--

通过颜色编码来完成表格中物料编码填写 part-no. completion for colour code	
颜色 / colour	编码 / code
黑色 / black	..00
蓝色 / blue	..01
棕色 / brown	..02
红色 / red	..03
白色 / white	..04
灰色 / grey	..05
紫色 / violet	..06
粉色 / pink	..07
橙色 / orange	..08
黄色 / yellow	..09
绿色 / green	..10
米色 / beige	..11
深蓝 / darkblue	..12
绿黄 / greenyellow	..99

举例 / example: 390 0005 1 00

公制 0,5mm², 导体: 镀锡铜丝,
护套颜色: 黑色

metrical 0,5mm², conductor: tinned copper,
sheath colour: black

robust cables
Schleppflex®
BUS cables
control cables
data cables
IT/communic.
high-temp.
lift cables
rubber cables
single cores
spiral cables
accessories
technical annex