


CC-Lift-2S-187

电梯电缆，带双根钢丝支撑

lift cable with two steel support wires



构造

CC-Lift-2S-187 特别适合作为电梯电缆和升降机吊机控制电缆，用于手动控制装置和输送带系统。两根外部钢丝支撑使其适用于需要自承式电缆的控制平台。耐候性极佳的外护套使其在极端运作和气候温度条件下能很好的使用。

application

The CC-Lift-2S-187 is particularly used as lift and hoist control cable in manual control units and conveyor systems. The two exterior steel wires support make it ideal for use on control platforms where self-supporting cables are needed, e.g., with high-lift storage shelving. The weather resistant outer sheath makes it excellent for use under extreme operation and temperature conditions.

构造

超细裸铜丝，PVC 芯线绝缘，黑色芯线连续白色数字编号并且带绿黄保护接地导体，芯线绞合节距短，编织带包覆。PVC 外护套，耐候性佳，阻燃和自熄（符合 DIN EN 60332-1-2 VDE 0482 332-1-2:2005-06 部分标准）。带两根支撑钢丝（每根抗拉强度大约 2000 N）钢丝与芯线分置单独排列，不会损坏外护套和芯线。外护套颜色为黑色。

construction

Superfine strands of bare copper wire, PVC core insulation, core colours are black with white numbering and greenyellow protective conductor in the outer layer, cores twisted in very short lay lengths, textile tape wrapping. Outer sheath based on cold-flexible PVC, weather resistant, flame retardant and self-extinguishing (acc. to DIN EN 60332-1-2 VDE 0482 part 332-1-2:2005-06). The two supporting steel wires (tear resistance per rope approx. 2000 N) are integrated in the outer sheath and are separable without damaging the outer sheath. Colour black.

技术数据 / technical data

额定电压 / rated voltage:	300/500 V
测试电压 / test voltage:	3.000 V
导体绞合方式 / conductor stranding:	超细铜丝绞合 / super fine copper strands, 符合 / acc. to DIN VDE 0295, 6 类标准 / class 6 min. 20 MOhm x km
绝缘阻抗 / insulation resistance:	移动应用 / flexible application: -15° C 至 /to +70° C
温度范围 / temperature range:	移动应用 / flexible application: 20 x d 外径 -ø / outer-ø
弯曲半径 / bending radius:	符合 / acc. to DIN VDE 0250, 0285
符合标准 / approvals:	

物料编码 part-no.	芯线数 / 导体截面积 / no. of cores / cross-section	铜重 copper weight kg/km	尺寸 dimension d x b mm	电缆重量 weight kg/km
187 0010 010	10 X 1,0*	96	15,0 x 27,1	416
187 0010 012	12 G 1,0	115	15,0 x 27,1	450
187 0010 018	18 G 1,0	173	17,2 x 32,1	530
187 0010 025	25 G 1,0	240	21,1 x 36,0	660
187 0010 030	30 G 1,0	288	22,0 x 39,2	765
187 0015 008	8 G 1,5	115	15,0 x 27,2	435
187 0015 012	12 G 1,5	173	16,6 x 31,6	510
187 0015 016	16 G 1,5	230	18,7 x 32,2	594
187 0015 018	18 G 1,5	260	19,2 x 32,0	678
187 0015 020	20 G 1,5	288	20,9 x 36,0	798
187 0015 024	24 G 1,5	346	22,5 x 37,0	900

* 不带绿黄接地导线，w/o gnye

robust cables
Schlepflex®
BUS cables
control cables
data cables
IT/communic.
high-temp.
lift cables
rubber cables
single cores
spiral cables
accessories
technical annex